

INFORMATION PROCESSING SYSTEM, MEDIUM,
INFORMATION PROCESSING APPARATUS, INFORMATION
PROCESSING METHOD, STORAGE MEDIUM STORING COMPUTER
READABLE PROGRAM FOR REALIZING SUCH METHOD

5

BACKGROUND OF THE INVENTION

Field of the Invention

200755397-021502

The present invention relates to an information
processing system for controlling the utilization of
10 digital contents, a medium, an information processing
apparatus, an information processing method, and a
storage medium storing a computer readable program for
realizing such a method.

Description of the Related Art

15 There are recent rapid advancements on preparation
and maintenance of optical fiber networks in a backbone
communication network, propagation of cable television
systems, practical use of satellite communications,
propagation of local area networks, and the like.
20 Interconnection of communication networks is vigorously
progressing. Digital contents can be exchanged
worldwide via such communication networks. The digital
contents include character data, audio data, still
image data, moving image data, computer programs and
25 the like.

Since a digital content is made of digital
information, the digital content can easily be copied.

Digital contents pose a problem of copyright protection.

In order to deal with this problem, techniques called "electronic watermark" are used. The

5 "electronic watermark" is techniques of processing a digital content in a predetermined manner to embed optional information in a digital content. The embedded information is hereinafter called "electronic watermark information".

10 If copyright information is embedded in a digital content as the electronic watermark information by utilizing the electronic watermark techniques, the digital content and copyright information can be processed independently so that the copyright can be

15 protected reliably.

A digital content embedded with electronic watermark information is received at a terminal such as a personal computer via, for example, an arbitrary communication network. If a user of a personal

20 computer activates a preinstalled program for sampling or deriving electronic watermark information, the electronic watermark information can be sampled from the digital content. In other words, the electronic watermark information can be sampled if a user wishes

25 to activate the sampling program.

If a malicious user utilizes a digital content without activating the sampling program or utilizes the

10075397 021502

digital content in the environment where the sampling
program cannot be activated, the function of copyright
protection cannot be realized because the electronic
watermark information cannot be sampled from the
5 digital content.

SUMMARY OF THE INVENTION

According to an embodiment of the invention, it is
an object to provide an information processing system
10 capable of controlling the utilization of a digital
content in accordance with electronic watermark
information sampled from the digital content, a medium,
an information processing apparatus, an information
processing method, and a storage medium storing a
15 computer readable program for realizing such a method.

Other objects and features of the present
invention will become apparent from the following
detailed description of the embodiments when read in
conjunction with the accompanying drawings.

20

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram showing the structure of
a network system according to the invention.

Fig. 2 is a block diagram showing the structure of
25 a digital content distribution server according a first
embodiment of the invention.

Fig. 3 is a flow chart illustrating an operation

10075397.021502

of the digital content distribution server according to the first embodiment of the invention.

Fig. 4 is a block diagram showing the structure of a client according to the first embodiment of the invention.

Fig. 5 is a flow chart illustrating an operation of the client according to the first embodiment of the invention.

Fig. 6 is a block diagram showing the structure of a digital content distribution server according to a second first embodiment of the invention.

Fig. 7 is a flow chart illustrating an operation of the digital content distribution server according to the second embodiment of the invention.

Fig. 8 is a block diagram showing the structure of the digital content distribution server according to the second first embodiment of the invention.

Fig. 9 is a block diagram showing the structure of a client according to the second embodiment of the invention.

Fig. 10 is a flow chart illustrating an operation of the client according to the second embodiment of the invention.

Fig. 11 is a block diagram showing the structure of another digital content distribution server according to the invention.

Fig. 12 is a block diagram showing the structure

10075597-001502

of a client according to the invention.

Fig. 13 is a block diagram showing the structure of a computer function of a digital content distribution server and client according to the invention.

Fig. 14 is a diagram showing an example of copyright information according to the invention.

Fig. 15 is a diagram showing an example of copyright information according to the invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Embodiments of the invention will be described with reference to the accompanying drawings.

[First Embodiment]

The invention is applied, for example, to a network system 100 such as shown in Fig. 1.

As shown in Fig. 1, the network system 100 of the embodiment has a structure that a digital content distribution server 110 and a terminal 120 on a user (client) side (hereinafter simply called a "client") are interconnected by a network 130 for the communications therebetween.

In Fig. 1, although one digital content distribution server 110 and one client 120 are connected via the network 130, a plurality of servers and clients may be interconnected.

The network system 100 of the embodiment is

configured so that when a digital content is utilized, the driving program added to the digital content automatically samples the electronic watermark information embedding in the digital content.

5 The digital content in this embodiment includes character data, audio data, still image data, moving image data, computer programs and the like.

10 The electronic watermark information in this embodiment is copyright information embedded in a digital content by using electronic watermark techniques, the copyright information being used for controlling the utilization of the digital content. The copyright information may be stored in a list storing permission information for each utilization mode, such as shown in Fig. 14. A digital content utilization control unit 123 of the client 120 to be later described refers to the copyright information sampled from a digital content and controls the utilization of the digital content in accordance with the permission information for each digital content utilization mode.

15

20

25 For example, the digital content utilization control unit 123 can control the utilization of a digital content by forcibly altering a subject file attribute of the digital content by referring to the sampled copyright information.

 The digital content utilization control unit 123

10075397.021502

can also control to permit the utilization of the digital content only by a particular application, by always monitoring applications utilizing the digital contents.

5 The digital content utilization control unit 123 can also control the utilization function (e.g., read, write, print, and etc.) of the digital content by always monitoring application program interface (API) used by various applications.

10 As shown in Fig. 14, if the digital content is constituted of audio objects and video objects, it is possible to control each object constituting the digital content. For example, it is possible to control not to permit edition of audio objects by
15 invalidating API which edits audio objects, or it is possible to control to permit edition of video objects by validating API which edits video objects.

 As shown in Fig. 15, copyright information may be stored in a list storing an authentication method, a
20 server uniform resource locator (URL) on the network 130 and a protocol. In this case, the digital content utilization control unit 123 controls the utilization of a digital content by accessing the server on the network 130 identified by URL by referring to the
25 copyright information sampled from the digital content, and by acquiring the permission information for each digital content utilization mode. A cipher key may be

10075397.D21502

acquired from the server to encipher the digital content by using the cipher key and distribute the enciphered digital content to another terminal.

100755397.0215002

A digital signature may be entered in the

5 copyright information to verify whether the sampled copyright information is legal. In this case, a verification station (not shown) is provided on the network system 100, which verifies whether the sampled copyright information is legal and notifies the

10 verification result to the client 120, a creator (not shown) of the digital content, the content distribution server 110 and the like.

The sampling program will be described which automatically samples electronic watermark information

15 embedded in a digital content.

The sampling program is created in such a manner that even if a digital content is copied, a copy of itself (driving program) is added to the copy of the digital content. The sampled program is automatically

20 activated when a digital content is executed. The sampling program depends on an operation system (OS) if the digital content is an executable file. If a digital content is stored in a storage medium such as a hard disc and a floppy disc, the sampling program is

25 added to the system area of the storage medium and depends upon the hardware architecture. If a digital content is data of particular application software, the

driving program depends upon the application software because it uses the macro functions of the application software.

Fig. 2 is a diagram showing the internal structure of the digital content distribution server 110 of the network system 100.

As shown in Fig. 2, the digital content distribution server 110 includes a digital content input unit 111, a sampling program addition unit 112, an electronic watermark embedding unit 113, and a communication unit 114.

The operation of the digital content distribution server 110 will be described with reference to Fig. 3.

Step S201: The digital content input unit 111 acquires a digital content in order to distribute it to the client 120 via the network 130. For example, this digital content was requested by the client 120 via the network 130 to the digital content distribution server 110.

Step S202: The sample program addition unit 112 adds the sampling program for sampling the electronic watermark information to the digital content acquired by the digital content input unit 111. This sampling program is so created that when the digital content is executed, the program automatically starts.

The sampling program may be embedded in the digital content by using electronic watermark

10075397-021502

techniques.

Step S203: The electronic watermark embedding unit 113 embeds the electronic watermark information in the digital content added with the sampling program by the sampling program addition unit 112.

Step S204: The communication unit 114 transmits the digital content added with the sampling program by the sampling program addition unit 112 and embedded with the electronic watermark information by the electronic watermark embedding unit 113, to the client 120 via the network 130.

In this embodiment, the digital content distribution server 110 adds the sampling program to the digital content (Step S202), and thereafter embeds the electronic watermark information (Step S203). It is therefore possible to transmit a digital content embedded with only the electronic watermark information and still not embedded with the sampling program.

The embodiment is not limited only to this process order. For example, the process order may be changed in accordance with a sampling program adding method, an electronic watermark information embedding method or the like.

Fig. 4 shows the internal structure of the client 120 of the network system 100.

As shown in Fig. 4, the client 120 has a communication unit 121, a digital content utilization

10075397.021502

unit 122, and a digital content utilization control unit 123.

The operation of the client 120 constructed as above will be described with reference to Fig. 5.

5 Step S211: The communication unit 121 receives a digital content from the digital content distribution server 110 via the network 130. This digital content was embedded with the electronic watermark information and added with the electronic watermark information
10 sampling program.

 Step S212: In response to an operation instruction from a user, the digital content utilization unit 122 processes (utilizes) the digital content received by the communication unit 121. In this case, at the same
15 time when the digital content is executed, the sampling program added to the digital content is activated. Therefore, at the same time when the digital content is utilized by the digital content utilization unit 122, the electronic watermark information embedded in the
20 digital content is automatically sampled.

 Step S213: In accordance with the electronic watermark information automatically sampled from the digital content, the digital content utilization control unit 123 controls the utilization of the
25 digital content. The control of the digital content utilization may include inhibiting the edition of a digital content as shown in the copyright information

100755307-024502

of Fig. 14, inhibiting the copy of a digital content, notifying the utilization of a digital content to the digital content distribution server 110 and the like. However, the embodiment is not limited only thereto.

5 In this embodiment, the utilization of a digital content is controlled by the digital content utilization control unit 123 of the client 120. The embodiment is not limited only thereto. For example, some control of a digital content may be performed by
10 the digital content utilization control unit 123 instead of making the control unit execute the whole of the control.

 More specifically, the control of a digital content may be performed by both the sampling program
15 added to the digital content and the digital content utilization control unit 123 in order to take partial charges of control functions. In this case, it is possible to prevent a malicious user (illegal user) of a digital content from disabling the digital content
20 utilization control unit 123 of the client 120 and illegally utilizing the digital content.

 Furthermore, rough utilization control such as permission and inhibition of utilization of a digital content may be performed by the sampling program,
25 whereas fine utilization control such as utilization contents (e.g., edition degree, edition allowed range, and etc.) of a digital content may be performed by the

100755397-021502

digital content utilization control unit 123. More specifically, when the sampling program samples the electronic watermark information representative of "utilization inhibition" of the digital content, the
5 sampling program may control to delete the digital content from the client 120.

In this embodiment, although a digital content is distributed to the digital content distribution server 110 and client 120 via the network 130, the digital
10 content may be distributed by storing it in a storage medium such as a CD-ROM, a floppy disc, a CD-R and a DVD, not limiting only to the communication medium such as the network 130.

As described above, in this embodiment, the
15 electronic watermark information and electronic watermark information sampling program are added to a digital content, and at the same time when the digital content is utilized, the sampling program added to the digital content is automatically activated.

It is therefore possible to always sample the
20 electronic watermark information embedded in the digital content and to reliably protect the copyright of the digital content.

In this embodiment, although the sampling program
25 is automatically activated when the digital content is utilized, a judgement unit for judging whether the sampling program is activated may be provided to

100755397.021502

restrict the utilization of a digital content in accordance with the judgement result. For example, if the judgement unit judges that the sampling program was not activated, the digital content is made unable to be
5 utilized, such as deletion thereof, or a message "there is a possibility of illegal action against the digital content" is notified to the digital content distribution server 110.

[Second Embodiment]

10 The structures and operations of a digital content distribution server 110 and a client 120 of the second embodiment will be described with reference to the accompanying drawings.

Similar to the first embodiment, the network
15 system 100 shown in Fig. 1 is applied to the second embodiment.

Fig. 6 shows the internal structure of the digital content distribution server 110 of the second
embodiment.

20 As shown in Fig. 6, the digital content distribution server 110 of the second embodiment is constituted of the constituent elements 111 to 114 shown in Fig. 2 and a program input unit 115.

The operation of the digital content distribution
25 server 110 constructed as above will be described with reference to Figs. 7 and 8.

Step S301: The digital content input unit 111

10075397-021502

acquires a digital content in order to distribute it to the client 120 via the network 130. For example, this digital content was requested by the client 120 via the network 130 to the digital content distribution server

5 110.

Step S302: The electronic watermark embedding unit 113 embeds the electronic watermark information in the digital content acquired by the digital content input unit 111.

10 Step S303: The communication unit 114 transmits the digital content embedded with the electronic watermark information by the electronic watermark embedding unit 113, to the client 120 via the network 130.

15 Step S304: The program input unit 115 of the digital content distribution server 110 acquires an application program in order to distribute it over the network 130. For example, this application program was requested by the client 120 via the network 130 to the
20 digital content distribution server 110. For example, the application program is a desk top publishing (DTP) program, a viewer program or the like.

Step S305: The sample program addition unit 112 adds the sampling program for sampling the electronic
25 watermark information to the application program acquired by the program input unit 115.

This sampling program is automatically executed

10075397-021502

when the application program is executed. The sampling program may be embedded in the application program by using electronic watermark techniques.

Step S306: The communication unit 114 transmits
5 the application program added with the sampling program by the sampling program addition unit 112, to the client 120 via the network 130.

Fig. 9 shows the internal structure of the client 120 of the second embodiment.

10 As shown in Fig. 9, the digital content distribution server 110 of the second embodiment is constituted of the constituent elements 121 to 123 shown in Fig. 4 and a program utilization unit 124.

The operation of the client 120 constructed as
15 above will be described with reference to Fig. 10.

Step S311: The communication unit 121 receives a digital content and an application program transmitted from the digital content distribution server 110 via the network 130. This digital content was embedded
20 with the electronic watermark information, and the application program was added with the sampling program for sampling the electronic watermark information from the digital content.

Step S312: In response to an operation instruction
25 from a user, the program utilization unit 124 activates the application program received by the communication unit 121, and the digital content utilization unit 122

10075397 0215002

processes (utilizes) the digital content received by the communication unit 121. In this case, at the same time when the application program is executed by the program utilization unit 124, the sampling program
5 added to the application program is automatically activated. Therefore, at the same time when the digital content is utilized by the digital content utilization unit 122, the electronic watermark information embedded in the digital content is
10 automatically sampled.

Step S313: In accordance with the electronic watermark information automatically sampled from the digital content, the digital content utilization control unit 123 controls the utilization of the
15 digital content. The control of the digital content utilization may include inhibiting the edition of a digital content, inhibiting the copy of a digital content, and the like. However, the embodiment is not limited only thereto.

20 In the second embodiment, the digital content distribution server 110 having the structure shown in Fig. 6 transmits separately the digital content embedded with the electronic watermark information and the application program added with the electronic
25 watermark information sampling program, to the client 120. The embodiment is not limited only thereto. For example, the integrated or combined digital content and

10075397-021502

application program may be transmitted.

For example, a file formed typically by MS-Word combines a main portion (digital content) of Ascii code trains and a supplemental information portion

- 5 (application program) such as attribute information and macro of the digital content. Such a file contains a plurality of digital contents in some cases.

- 10 In such cases, as shown in Fig. 11, the digital content distribution server 110 is provided with a combining unit 116 which combines the digital content embedded with copyright information output from the electronic watermark embedding unit 113 and the application program with the sampling program output from the sampling program addition unit 112, and
- 15 supplies the combined digital content and application program to the communication unit 114. In this manner, a file combining the digital content and application program can be distributed. The combining unit 116 can distribute a single file combining an application
- 20 program output from the sampling program addition unit 112 and a plurality of digital contents output from the electronic watermark embedding unit 113.

- As shown in Fig. 12, in accordance with the copyright information of each digital content sampled
- 25 by the sampling program, the digital content utilization control unit 122 of the client 120 controls the utilization of each digital content by the program

10075397-021502

utilization unit 124.

In this manner, even if a file contains a plurality of digital contents, the utilization control can be performed one digital content after another.

5 As described above, in this embodiment, if a digital content is utilized by using an application program such as a DTP program and a viewer program, at the same time when the application program starts, the sampling program added to the application program
10 automatically starts.

It is therefore possible to reliably sample the electronic watermark information from a digital content when the digital content is utilized by using an application program.

15 In the second embodiment, a digital content can be utilized by starting an application program added with the sampling program. The invention is not limited only to the case wherein a digital content can be utilized by directly activating an application program
20 added with the sampling program.

Recent application programs are highly sophisticated, and many applications are divided into libraries, plug-in and the like for respective functions. In such a case, the sampling program may be
25 added to the library, plug-in and the like to be activated by the application program.

Furthermore, if the sampling program is added only

10075397.0215002

to a single program, there may occur the case that this single program is not activated. In order to avoid this, the sampling program may be added to a program having a high activation frequency or to a plurality of programs.

In this embodiment, although a digital content and an application program are distributed to the digital content distribution server 110 and client 120 via the network 130, the digital content and application program may be distributed by storing them in a storage medium such as a CD-ROM, a floppy disc, a CD-R and a DVD, not limiting only to the communication medium such as the network 130.

[Other Embodiments]

It is obvious that the objects of the invention can be realized by supplying an apparatus or system with a storage medium storing software program codes realizing the functions of the host and terminal of the first and second embodiments and by making a computer (or CPU or MPU) of the apparatus or system read and execute the program codes.

In this case, the software program codes themselves read from the storage medium realize the functions of the first and second embodiments.

Therefore, the storage medium storing the program codes constitutes the present invention.

The storage medium for storing such program codes

10075397.021502

may be a ROM, a floppy disk, a hard disk, an optical disk, a magneto optical disk, a CD-ROM, a CD-R, a magnetic tape, a nonvolatile memory card, or the like.

It is obvious that the scope of the invention
5 contains the case wherein not only the functions of the first and second embodiments are realized by executing the program codes read by a computer but also the functions of the first and second embodiments are realized by making an OS or the like running on a
10 computer perform a portion or the whole of the actual processes in accordance with the program codes.

It is obvious that the scope of the invention also contains the case wherein the functions of the first and second embodiments can be realized by writing the
15 program codes into a memory of a function expansion board inserted into a computer or of a function expansion unit connected to the computer, and thereafter by making a CPU of the function expansion board or function expansion unit execute a portion or
20 the whole of actual processes.

Fig. 13 shows an example of the structure of a computer function 600. Each of the digital content distribution server 110 and client 120 is provided with the computer function 600, and a CPU 601 operates to
25 realize the operations of the first and second embodiments.

As shown in Fig. 13, the compute function 600 is

100755397-0215002

realized by CPU 601, a ROM 602, a RAM 603, a keyboard controller (KBC) 605 for a keyboard (KB) 609, a CRT controller (CRTC) 606 for a CRT display (CRT) 610 as a display unit, a disc controller (DKC) 607 for a hard disc (HD) 611 and a floppy disc (FD) 612, and a network interface card (NIC) 608, respectively connected by a system bus 604 for communications among them.

The network interface card (NIC) 608 is connected to a network 640 such as the network 130 shown in Fig. 1.

CPU 601 executes software stored in ROM 602 or HD 611 or software supplied from FD 612 to collectively control the constituent elements connected to the system bus 604.

CPU 601 reads a program satisfying a predetermined process sequence from ROM 602, HD611, or FD 612 and executes it to realize the operations of the first and second embodiments.

RAM 603 functions as the main memory, working area and the like of CPU 601. KBC 605 controls inputs supplied from an unrepresented pointing device or the like. CRTC 606 controls a display of CRT 610.

DKC 607 controls an access to HD 611 and FD 612 which store a boot program, various applications, editor files, user files, network management programs and predetermined programs for realizing the functions of the embodiments. NIC 608 transfers data to and from the apparatus or system on the network 140.

10075397-021502